TSA 160 WC-compartments for disabled persons

Functional description

- ► After the pad switch ② has been operated, the toilet door opens and closes automatically upon lapse of a presettable hold-open time.
- ▶ By operating the changeover switch ⑥ inside the toilet cabin, the user activates the illuminated sign "OCCUPIED" ⑥ outside the compartment as well as the control lamp ⑥ at the changeover switch.

 Simultaneously the interior and exterior pad switch ⑥ is switched off. thus the door can neither be opened by a third person nor by the user himself by accident.


The live door opener prevents that the door can be opened manually.

➤ To leave the lavatory, the user again operates the changeover switch **6**, the sign "OCCUPIED" outside the compartment as well as the control lamp go out.

By operating the interior pad switch "DOOR OPEN" **3** the door will immediately open.

- ▶ In the case of power failure the user has the possibility to open the door manually by pushing or pulling it open, the closed-circuit opener is unlocked.
- ► The door can also be opened from inside by operating the door handle even if the system is live.
- ► In an emergency the door can also be manually opened from outside using a key or by operating the emergency cutout **⑤**.





TSA 160 WC-compartment for disabled persons

- Swing door actuator TSA 160
- 2 Pad switch "DOOR OPEN", outside
- 3 Illuminated sign "OCCUPIED", outside
- Emergency cutout
- 6 Door opener
- **6** Changeover switch locked / unlocked
- Illuminated sign "OCCUPIED", inside
- 8 Pad switch "DOOR OPEN", inside